

Technical Data Sheet

MOGAS 2T MOTOR OIL
2-STROKE ENGINE OIL



Description:

MOGAS 2T Motor oil is a mineral based lubricant designed for use in 2- stroke engines when premixed with petrol.

Application:

For use in standard two-stroke petrol engines of motorcycles, scooters, lawn mowers and similar small engines. Oil is to be mixed with fuel in ratio according to manufacturer’s recommendations.

Specification and Approvals:

JASO FB / ISO-L-EGB

Benefits:

- Improved miscibility between oil and fuel
- Controls deposits on spark plugs and in combustion chamber
- Clean combustion.

Health, Safety and Environment:

This product, when used as per our recommendation for the intended application, is not expected to produce any particular risk. A Material Safety Data Sheet of it is available upon request from our local sales contact office or on our website. In case of used oil disposal, please respect the Regulations for protecting the environment.

Typical Properties:

Test Parameters	Units	Test Method	Mean Values
SAE Grade			SAE 20
Viscosity at 40°C	mm ² /s	ASTM D 445	58.09
Viscosity at 100°C	mm ² /s	ASTM D 445	8.32
Viscosity Index	-	ASTM D 2270	114
Total Base Number	mgKOH/g	ASTM D 2896	Min, 1.0
Pour Point	°C	ASTM D 97	-27
Flash Point (COC)	°C	ASTM D 92	160
Density at 20°C	Kg/m ³	ASTM D 4052	86

MOGAS GROUP - CORPORATE OFFICE
 40 Nile Avenue, P.O. Box 19, Kampala, Uganda.
www.mogasoil.com

Due to continual product research and development, the information contained herein is subject to change without notification. © Copyright 2017. All rights reserved | Last edited: April 2025 – V4