


## Technical Data Sheet

# MOGAS SENTRY 4T SAE 20W-50

## Tri-Guard 4-Stroke Motorcycle Oil



### Description:

MOGAS Sentry 4T is a premium quality SAE 20W-50 oil specially formulated to satisfy the needs of tri-zone lubrication of the engine, wet clutch and gearbox of 4-stroke motorcycles, to ensure durable protection and reliable efficient performance.

### Application:

For use in all 4-stroke engine motorcycles of Japanese, Chinese, Indian and European makes, operating in all conditions - normal riding, busy city traffic, off-road or sporting activities.

### Specification and Approvals:

API SL, JASO MA2

### Benefits:

- High-temperature and high-shear viscosity stability ensures exceptional engine protection against scuffing and accelerated wear, enabling maximum reliability and prevention of costly downtime.
- The technically advanced Viscosity Improver allows easy engine start-up, power output and fuel economy.
- The high technology anti-wear additive helps easy gearshifts, reduced wear and smooth riding.
- Superior detergency and dispersancy protects the engine against sludge and varnish formation.
- The balanced additive package system provides proper frictional properties to avoid clutch slip.
- Good resistance to foaming and air entrainment for efficient lubrication.

### Health, Safety And Environment:

This product, when used as per our recommendation for the intended application, is not expected to produce any particular risk. A Material Safety Data Sheet of it is available upon request from our local sales contact office or on our website. In case of used oil disposal, please respect the Regulations for protecting the environment.

### Typical Characteristics:

Test Parameters	Units	Test Method	Mean Values
SAE Grade			20W-50
Viscosity at 40°C	mm <sup>2</sup> /s	ASTM D 445	151.8
Viscosity at 100°C	mm <sup>2</sup> /s	ASTM D 445	17.77
Viscosity Index	-	ASTM D 2270	129
Total Base Number	mg KOH/g	ASTM D 2896	8.3
Pour Point	°C	ASTM D 97	-24
Flash Point (Cleveland)	°C	ASTM D 92	232
Density at 15°C	Kg/m <sup>3</sup>	ASTM D 4052	865

**MOGAS GROUP - CORPORATE OFFICE**  
40 Nile Avenue, P.O. Box 19, Kampala, Uganda.  
[www.mogasoil.com](http://www.mogasoil.com)

Due to continual product research and development, the information contained herein is subject to change without notification. © Copyright 2017. All rights reserved | Last edited: February 2025 – V4